

Unrestrained Storage and Connection

Data storage no longer be bound by transmission wires



GDM-8300 Series

3 Year WARRANTY

50000 Counts Dual Measurement Multimeter

- 50000 Counts Vacuum Fluorescent Display with Two Colors
- Dual Measurement
- Fast Measurement Rate Up to 40 readings/s for DCV
- 0.02% DCV Basic Accuracy
- Auto/Manual Ranging
- True RMS (AC, AC+DC)
- 11 Measurement Functions
- Max./Min.,REL,MX+B,1/X,Ref %,Compare,Hold,dB,dBm
- Standard USB device for communicating to PC
- Temperature Measurement (GDM-8342 only)
- USB Storage for Data Collection (GDM-8342 only)
- Optional GPIB (factory install for GDM-8342 only)



www.gwinstek.com

GW INSTEK
Simply Reliable

SPECIFICATIONS *1*2

DC CHARACTERISTICS

DC VOLTAGE

| Range(*3) | Resolution | Input Resistance | Accuracy 1 Year (23°C±5°C) |
|-----------|------------|------------------|----------------------------|
| 500.00mV | 10µV | 10MΩ or >10GΩ | 0.02 + 4 |
| 5.0000V | 100µV | 10MΩ or >10GΩ | 0.02 + 4 |
| 50.000V | 1mV | 11.1MΩ | 0.02 + 4 |
| 500.00V | 10mV | 10.1MΩ | 0.02 + 4 |
| 1000.0V | 100mV | 10MΩ | 0.02 + 4 |

RESISTANCE

| Range(*3) | Resolution | Test Current | Accuracy 1 Year (23°C±5°C) |
|-----------|------------|--------------|----------------------------|
| 500.00Ω | 10mΩ | 0.83mA | 0.10 + 5 (*4) |
| 5.0000kΩ | 100mΩ | 0.83mA | 0.10 + 3 (*4) |
| 50.000kΩ | 1Ω | 83µA | 0.10 + 3 |
| 500.00kΩ | 10Ω | 8.3µA | 0.10 + 3 |
| 5.0000MΩ | 100Ω | 830nA | 0.10 + 3 |
| 50.000MΩ | 1kΩ | 560nA//10MΩ | 0.30 + 3 |

DC CURRENT

| Range(*3) | Resolution | Burden Voltage | Accuracy 1 Year (23°C±5°C) |
|-----------|------------|----------------|----------------------------|
| 500.00µA | 10nA | 0.06Vmax. | 0.05 + 5 |
| 5.0000mA | 100nA | 0.6Vmax. | 0.05 + 4 |
| 50.000mA | 1µA | 0.14Vmax. | 0.05 + 4 |
| 500.00mA | 10µA | 1.4Vmax. | 0.10 + 4 |
| 5.0000A | 100µA | 0.5Vmax. | 0.25 + 5 |
| 10.000A | 1mA | 0.8Vmax. | 0.25 + 5 |

CONTINUITY

| Range(*3) | Resolution | Test Current | Accuracy 1 Year (23°C±5°C) |
|-----------|------------|--------------|----------------------------|
| 5000.0Ω | 100mΩ | 0.83mA | 0.10 + 5 |

DIODE TEST (*7)

| Range(*3) | Resolution | Test Current | Accuracy 1 Year (23°C±5°C) |
|-----------|------------|--------------|----------------------------|
| 5.0000V | 100µV | 0.83mA | 0.05 + 5 |

CAPACITANCE

| Range(*3) | Resolution | Test Current | Accuracy 1 Year (23°C±5°C) |
|-------------------|------------|--------------|----------------------------|
| 5.000nF : 0.5~1nF | 0.001nF | 8.3µA | 2.00 + 20 |
| 5.000nF : 1~5nF | 0.001nF | 8.3µA | 2.00 + 10 |
| 50.00nF : 5~10nF | 0.01nF | 8.3µA | 2.00 + 30 |
| 50.00nF : 10~50nF | 0.01nF | 8.3µA | 2.00 + 10 |
| 500.0nF | 0.1nF | 83µA | 2.00 + 4 |
| 5.000µF | 1nF | 0.56mA | 2.00 + 4 |
| 50.00µF | 10nF | 0.83mA | 2.00 + 4 |

FREQUENCY AND PERIOD CHARACTERISTICS

FREQUENCY / PERIOD

| Range | Accuracy 1 Year (23°C±5°C) |
|----------------|----------------------------|
| 10Hz ~ 500Hz | 0.01 + 5 |
| 500Hz ~ 500kHz | 0.01 + 3 |
| 500kHz ~ 1MHz | 0.01 + 5 |

General

| | |
|---------------------|--|
| Display | VFD, Two Colors Display |
| Interface | USB device, USB Host (GDM-8342 only) |
| Power Source | AC 100 V / 120 V / 220 V / 240 V ±10%, 50-60Hz |
| Power Consumption | Max. 15VA |
| Dimensions & Weight | 265(W) x 107(H) x 302(D) mm, approx. 2.9kg |

ORDERING INFORMATION

| | |
|---------------------------|---|
| GDM-8342 with GPIB | 50000 counts Dual Measurement Multimeter with USB Host/Device and opt.01 GPIB |
| GDM-8342 | 50000 counts Dual Measurement Multimeter with USB Host/Device |
| GDM-8341 | 50000 counts Dual Measurement Multimeter with USB Device |

ACCESSORIES

Safety Instruction Sheet x 1, Power cord x 1, Test lead GTL-207 x 1, CD x 1 (including complete user manual, USB driver and PC software)

AC CHARACTERISTICS

True RMS AC (or AC+DC – AC Coupled) Voltage (*5*6)

| Range(*3) | Resolution | Frequency | Accuracy 1 Year (23°C±5°C) |
|-----------|------------|--|---|
| 500.00mV | 10µV | 30Hz ~ 50Hz 50Hz ~ 10kHz 10kHz ~ 30kHz 30kHz ~ 100kHz | 1.00 + 40 0.50 + 40 2.00 + 60 3.00 + 120 |
| 5.0000V | 100µV | 30Hz ~ 50Hz 50Hz ~ 10kHz 10kHz ~ 30kHz 30kHz ~ 100kHz | 1.00 + 20 0.35 + 15 1.00 + 20 3.00 + 50 |
| 50.000V | 1mV | 30Hz ~ 50Hz 50Hz ~ 10kHz 10kHz ~ 30kHz 30kHz ~ 100kHz | 1.00 + 20 0.35 + 15 1.00 + 20 3.00 + 50 |
| 500.00V | 10mV | 30Hz ~ 50Hz 50Hz ~ 10kHz 10kHz ~ 30kHz 30kHz ~ 100kHz | ---- 0.50 + 15 1.00 + 20 3.00 + 50 |
| 750.0V | 100mV | 30Hz ~ 50Hz 50Hz ~ 10kHz 10kHz ~ 30kHz 30kHz ~ 100kHz | ---- 0.50 + 15 ---- ---- |

True RMS AC (or AC+DC – AC Coupled) Current (*5*6)

| Range(*3) | Resolution | Frequency | Accuracy 1 Year (23°C±5°C) |
|-----------|------------|---|--|
| 500.00µA | 10nA | 30Hz ~ 50Hz 50Hz ~ 2kHz 2kHz ~ 5kHz 5kHz ~ 20kHz | 1.50 + 50 0.50 + 40 1.50 + 50 3.00 + 75 |
| 5.0000mA | 100nA | 30Hz ~ 50Hz 50Hz ~ 2kHz 2kHz ~ 5kHz 5kHz ~ 20kHz | 1.50 + 40 0.50 + 20 1.50 + 40 3.00 + 60 |
| 50.000mA | 1µA | 30Hz ~ 50Hz 50Hz ~ 2kHz 2kHz ~ 5kHz 5kHz ~ 20kHz | 1.50 + 40 0.50 + 20 1.50 + 40 3.00 + 60 |
| 500.00mA | 10µA | 30Hz ~ 50Hz 50Hz ~ 2kHz 2kHz ~ 5kHz 5kHz ~ 20kHz | 1.50 + 40 0.50 + 20 1.50 + 40 3.00 + 60 |
| 5.0000A | 100µA | 30Hz ~ 50Hz 50Hz ~ 2kHz | 2.00 + 40 0.50 + 30 |
| 10.000A | 1mA | 30 z ~ 50Hz 50Hz ~ 2kHz | 2.00 + 40 0.50 + 30 |

TEMPERATURE CHARACTERISTICS

THERMOCOUPLES

| Type | Range | Resolution | Accuracy(*7) 1 Year (23°C±5°C) |
|-----------|-------------------|------------|--------------------------------|
| J / T / K | -200 °C ~ +300 °C | 0.1 °C | 2 °C |

Note: The specifications apply when the DMM is warmed up for at least 30 minutes and operates in slow rate.

1. All specifications are ensured only under main (1st) display.
2. Accuracy : ± (% of reading + digits)
3. 2% overrange on all ranges, except 10A.is 20% overrange.
4. REL function is on.
5. The accuracy of AC+DC is equal to AC with 10 more digits added.
6. AC Characteristics are for sinewave input > 5% of range.
7. Specifications do not include probe accuracy.

Specifications subject to change without notice.

DM-8300GD1DH

OPTION

Opt.1 GPIB Interface

OPTIONAL ASSESSORIES

| | |
|----------------|--|
| GTL-205 | Temperature probe adaptor with thermocouple (K-type), Approx. 1000mm |
| GTL-246 | USB Cable, A-B type, Approx. 1200mm |
| GTL-251 | GPIB-USB-HS (high Speed) |

Global Headquarters

GOOD WILL INSTRUMENT CO., LTD.

No.7-1, Jhongsing Road, Tucheng Dist., New Taipei City 236, Taiwan
T +886-2-2268-0389 F +886-2-2268-0639
E-mail: marketing@goodwill.com.tw

China Subsidiary

GOOD WILL INSTRUMENT (SUZHOU) CO., LTD.

No. 521, Zhujiang Road, Snd, Suzhou Jiangsu 215011 China
T +86-512-6661-7177 F +86-512-6661-7277
E-mail: marketing@instek.com.cn

Malaysia Subsidiary

GOOD WILL INSTRUMENT (M) SDN. BHD.

27, Persiaran Mahsuri 1/1, Sunway Tunas,
11900 Bayan Lepas, Penang, Malaysia
T +604-6309988 F +604-6309989
E-mail: sales@goodwill.com.my

U.S.A. Subsidiary

INSTEK AMERICA CORP.

3661 Walnut Avenue Chino, CA 91710, U.S.A.
T +1-909-591-8358 F +1-909-591-2280
E-mail: sales@instekamerica.com

Japan Subsidiary

INSTEK JAPAN CORPORATION

2F DSM Shin-Yokohama Bldg. 2-6-3, Shin Yokohama, Kouhoku-ku,
Yokohama, Kanagawa 222-0033 Japan
T +81-45-476-5650 F +81-45-476-5653
E-mail: info@instek.co.jp

Korea Subsidiary

GOOD WILL INSTRUMENT KOREA CO., LTD.

#1406, Ace Hightech-City B/D 1Dong,
Mullae-Dong 3Ga 55-20, Yeongduengpo-Gu, Seoul, Korea
T +82-2-3439-2205 F +82-2-3439-2207
E-mail: gwinstek@gwinstek.co.kr

Distributed By:

Signal Test, Inc
1529 Santiago Ridge Way
San Diego, CA 92154
Tel. 1-619-575-1577 USA
www.SignalTestInc.com
Sales@SignalTestInc.com

GW INSTEK

Simply Reliable

www.gwinstek.com