

Distributed By:
 Signal Test, Inc
 1529 Santiago Ridge Way
 San Diego, CA 92154
 Tel. 1-619-575-1577 USA
 www.SignalTestInc.com
 Sales@SignalTestInc.com



SPECIFICATIONS	
	GCP-020
Bandwidth	40Hz ~ 10kHz
Ratio	100mA ~ 20A 500mA ~ 200A
Accuracy	≤ 2% (100mA ~ 20A peak) ≤ 1.5% (500mA ~ 200A peak)
Nominal Measuring Scope	500mA ~ 200A and 100mA ~ 20A
Ratio Input/Output	1A ~ / 10mV ~ and 1A ~ / 1000mV
Sinusoidal Current	48 ~ 65Hz
Connection	BNC
Direct Current	No
Temperature & Humidity Range (Guaranteed Accuracy)	20 ~ 26°C, relative humidity ; 20 ~ 75% (no condensation)
Continuous Magnetic Field	Earth Field (< 40A / m)
Proximity of External Conductors	No current
Measuring Device Impedance	> 1 MW and < 100pF
Max. Clamping Capacity	∅20mm cable or 20 x 5mm bar
Location for Use	Altitude up to 2000m, Indoors
Dimension	135(W) x 50(H) x 30(D) mm
Open Jaw Height	69mm
Weight	Approx. 180g
Jaw Opening	21mm