Distributed By:
Signal Test, Inc
1529 Santiago Ridge Way
San Diego, CA 92154
Tel. 1-619-575-1577 USA
www.SignalTestInc.com
Sales@SignalTestInc.com



Use the PB-503 to construct a wide variety of experiments, including but not limited to:

**Opto-Device Circuits** 

Clocks

Multivibrators

**Oscillator Circuits** 

Timers

**Function Generator Circuits** 

Logic Circuits

Gates

Counters

Flip-Flops

Analog-to-Digital Converters

Digital-to-Analog Converters

Medium Scale Integration Circuits

Phase Lock Loops

**Operational Amplifier** 

## **Trainer Series**

## Electronic Trainers

## PB-503 Analog & Digital Design Workstation



Features:

Ideal for analog, digital and microprocessor circuits

Includes built-in Function Generator with continuously variable waveforms

Triple output power supply for a variety of DC voltage levels

Two Digital Pulsers for logic test circuits High & low buffered logic indicators

8 channel logic monitor

Audio experimentation speaker

Removable breadboard plate allows the flexibility of building circuits away from the lab

Analog & Digital optional courseware available Input Power Source, AC Line: Switchable between 110-120VAC @ 60Hz & 210-220VAC @ 50Hz

3-year warranty on all parts and workmanship.

Global Specialties Model PB-503 is an Analog & Digital Design Workstation. The PB-503's newly updated, robust design makes it a trainer suitable for all levels of electronics instruction and design.

The PB-503's breadboarding area is comprised of Global's "Premium" solderless breadboards and is backed by an industry leading 3-year warranty.

The PB-503 can be used to construct basic series and parallel circuits up to the most complicated multi-stage microcomputer circuits, incorporating the latest in industrial technology.

The PB-503 allows students to learn valuable hands-on lab experience by employing necessary breadboarding techniques, which provide a solid foundation in circuit experimentation, analyzing and troubleshooting.

Experienced designers will also find the PB-503 an invaluable, capable and reliable instrument, suitable for the most advanced and demanding design applications.

Global Specialties trainers provide the most complete platform required to enable engineers and technicians to train for careers in the rapidly growing field of electronics technology.



Innovative Training Solutions

www.globalspecialties.com

# **Trainer Series**

### Electronic Trainers

# Analog & Digital Design Workstation

# **Specifications**

Model	
Model	PB-503
	FB-303
Input power Source	Input Power Source, AC Line: Switchable between 110-120VAC @ 60Hz & 210-220VAC @50Hz
Power Supplies	Fixed DC: +5VDC 1.0A max, current limited Ripple, <5mV Variable + DC: +1.3V @150mA to +15VDC @ 500mA , Ripple < 5mV Variable - DC: -1.3VDC @ 150mA to -15VDC @ 500mA, Ripple < 5mV
Binding Posts	(4) Ground, +5 VDC, Variable + DC & Variable - DC Power Supply Outputs
Pulsers	(2) Pushbutton-operated, open-collector output pulsers. Each with 1 normally-open, 1 normally-closed output. Each output sinks up to 250 mA
Function Generator	Frequency Range: $0.1Hz$ to $100KHz$ , six ranges Output Voltage: $0$ to $\pm$ $10Vp$ -p into $50$ $\Omega$ Load ( $20Vp$ -p in open circuit), short circuit protected Output Impedance: $600\Omega$ except TTL Output waveforms: Sine, Square, Triangle & TTL Sine Wave Distortion: <3% @ 1Khz Typical TTL Pulse: Rise & fall time: <25ns, drive $10$ TTL Loads ( $TTL$ is available when the function generator is set to Square Wave Mode) Square Wave: Rise and fall times <0.5 $\mu$ s
Logic Switches	(8) Logic Switches select Logic High and Logic Low Logic Low Level: Ground Logic High Level: Switchable between +5V and the variable positive power supplies.
Switches	(2) Single Pull Double Throw (SPDT) - uncommitted
Logic Indicators	LEDs: 16 LEDs; (8) red to indicate logic high and (8) green to indicate logic low Logic High Threshold: 2.2V (nominal) in TTL/+5V mode, 70% (nominal) of selected operating voltage in CMOS mode Logic Low Threshold: 0.8V (nominal) in TTL/+5V mode, 30% (nominal) of selected operating voltage in CMOS mode
Connectors	2 ea BNC - uncommitted
Potentiometers	2: $1 \text{ k}\Omega$ and $10 \text{ k}\Omega$ - uncommitted
Speaker	8 Ω, 0.25 W - uncommitted
Breadboards	Removable Plexiglas Socket Plate (PB-3) with 2520 Tie points with 200 additional buss strip tie points internally connected to power supply outputs and ground
Weight	7 lbs (3.2 kg)
Dimensions	6.5 x 16 x 11.5" (165 x 406 x 292 mm)
Dimensions	0.0 % 10 % 11.0 (100 % 700 % 202 IIIIII)

Technical data subject to change without notice.



### **Optional Accessories**

Courseware: Available separately or as a package (Model PB-503 Lab).

WK-1: Jumper Wire Kit, 350 pieces WK-2: Jumper Wire Kit, 140 pieces

WK-3: Jumper Wire Kit, 70 pieces WK-4: Wire Jumper Kit, 100 wires with

machined tips

**GSPA Series:** Prototyping adapters GSPA-K1: Surface mount to DIP adapter

kit, 6 adapter boards

GSPA-K2: Surface mount to DIP adapter

kit. 11 adapter boards GSA-3185: Minipro Test Clip Set PRO-50A: Digital Multimeter

The PB-503 Lab package offers comprehensive course instruction covering the following areas:

#### **Electronic Fundamentals**

Fundamentals of Electricity Ohm's Law Series Circuits, Parallel Circuits Combinational Circuits Current Control Closed, open, shorts Switches

Thevenin's Theorem Wheatstone Bridge Capacitors, Inductors **Phase Shift Circuits** Impedance Resonant Circuits Transformers

Rectifiers & Filtering Integrated Circuits

**Transistor Amplifiers** 

Oscillators

**Power Control Circuits** 

#### **Digital Electronics**

Number Systems & Codes Binary, Decimal, Hexadecimal, Octal & **ASCII** 

Logic Gates & Boolean Algebra Combinational Logic Circuits

Flip-Flops

Digital Arithmetic Counters & Registers

Integrated Circuit Logic Families

TTL Logic **MOSFETS** 

**CMOS** 

Interfacing CMOS & TTL Medium Scale Integration

Decoders

**Encoders** 

Data Conversion & Acquisition Microcomputer Concepts