

### Constant Voltage Mode

CVH Range	0.000 ~ 600.0	V
CVM Range	0.000 ~ 300.0	V
CVL Range	0.000 ~ 60.00	V
Transient Time Range		
Fast Band(Default,Osc1)	0.500 ~ 51.19	ms
Slow Band(Osc2,Osc3)	0.500 ~ 511.9	ms
Temperature Coefficient	100 ppm / °C of Rated Voltage	
<b>Program</b>		
CV Resolution*2	1/16000 of Rated Voltage	
CVH Accuracy*2	0.05% ± 0.600	V
CVM Accuracy*2	0.05% ± 0.600	V
CVL Accuracy*2	0.05% ± 0.600	V
<b>Display</b>		
CVH Resolution	1/16000 of Rated Voltage	
CVH Accuracy	0.05% ± 0.600	V
CVM Accuracy	0.05% ± 0.600	V
CCL Accuracy	0.05% ± 0.600	V

### Constant Current Mode

CCH Range	0.000 ~ 120.0	A
CCM Range	0.000 ~ 60.00	A
CCL Range	0.000 ~ 12.00	A
Transient Time Range		
Fast Band(Default,Osc1)	0.050 ~ 51.19	ms
Slow Band(Osc2,Osc3)	0.500 ~ 511.9	ms
Minimum Voltage(I <sub>Max</sub> )	4.500	V
Temperature Coefficient	100 ppm / °C of Rated Current	
<b>Program</b>		
CC Resolution*2	1/16000 of Rated Current	
CCH Accuracy*2	0.05% ± 0.120	A
CCM Accuracy*2	0.05% ± 0.120	A
CCL Accuracy*2	0.05% ± 0.120	A
<b>Display</b>		
CC Resolution	1/16000 of Rated Current	
CCH Accuracy	0.05% ± 0.120	A
CCM Accuracy	0.05% ± 0.120	A
CCL Accuracy	0.05% ± 0.120	A

### Programmable Protection

Power(OPP)		
Range	3.438 ~ 2,750	W
Resolution	0.344	W
Accuracy	0.50% ± 6.875	W
Voltage(OVP)		
Range	0.394 ~ 630.0	V
Resolution	0.039	V
Accuracy	0.20% ± 0.788	V
Current(OC)		
Range	0.079 ~ 126.0	A
Resolution	0.008	A
Accuracy	0.20% ± 0.158	A
Under Voltage Lockout(UVL)		
Mode	Input On / Continuous	
Range	0.450 ~ 600.0	V
Resolution	0.150	V
Accuracy	2.50% ± 0.750	V
Anti-Oscillation	Default / Osc1 / Osc2 / Osc3 / Disable	

### Protection

Over Power Protection(OP)	2,750 ± 52.38	W
Over Voltage Protection(OV)	630.0 ± 12.00	V
Over Current Protection(OC)	132.0 ± 1.257	A
Over Temperature Protection(OTP)	90.00 ± 5.000	°C
Reverse Maximum Current(RCP)	132.0	A
Short Maximum Current	122.4	A
Remote Inhibit(RI)	Short	
Fault Indicator	SPDT Relay (30Vdc/0.5A or 125Vac/0.25A)	

### Dielectric Strength

Primary Circuit To Chassis	1500 Vac for 1 min
Primary Circuit To Load Terminal	1500 Vac for 1 min
Load Terminal To Chassis	1500 Vdc for 1 min

### Constant Power Mode

CPH Range	0.000 ~ 2,500	W
CPM Range	0.000 ~ 1,250	W
@ lin	≤ 60.00	A
CPL Range	0.000 ~ 250.0	W
@ lin	≤ 12.00	A
Transient Time Range		
Same As CC Mode		
Temperature Coefficient	300 ppm / °C of Rated Power	
<b>Program</b>		
CP Resolution*2	1/16000 of Rated Power	
CPH Accuracy*2	1.00% ± 12.50	W
@lin	> 6.000	A
& Vin	> 60.00	V
CPM Accuracy*2	1.00% ± 12.50	W
@lin	> 1.200	A
& Vin	> 60.00	V
CPL Accuracy*2	1.00% ± 12.50	W
@lin	> 0.120	A
& Vin	> 120.0	V

### Constant Resistance Mode

CRH Range	50.00 ~ 2,500	Ω
@ lin	≤ 12.00	A
CRM Range	5.000 ~ 1,250	Ω
CRL Range	0.0375 ~ 5.000	Ω
Transient Time Range		
CRM / CRH	Same As CC Mode	
CRL	Same As CV Mode	
Temperature Coefficient		
CRM / H	300 ppm / °C of Minimum Resistance	
CRL	300 ppm / °C of Maximum Resistance	
<b>Program</b>		
CR Resolution*2	1/16000 Of Rated Value	
CRH Accuracy*2	1.00% ± 0.100	mS
@lin	> 0.120	A
& Vin	> 120.0	V
CRM Accuracy*2	1.00% ± 0.400	mS
@lin	> 1.200	A
& Vin	> 60.00	V
CRL Accuracy*2	1.00% ± 5.000	mΩ
@lin	> 12.00	A
& Vin	> 0.600	V

### External Programming Mode

Analog Program	0~10 Volts Input yields 0~selected full scaled loading in all modes
Accuracy	Same As Internal ± 0.1% Rating
Input Impedance	400 kΩ ± 1%
BandWidth(-3dB)	Limited By Internal Transient Time
Monitor output Signal	0~10 Volts output for 0~full scaled Value
VMON Accuracy	0.10% ± 0.600 V
IMON Accuracy	0.10% ± 0.120 A
Transient Mode	
Frequency Range	0.100 ~ 10,000 Hz
Accuracy	0.1%
Duty Range	1.000 ~ 100.0 %
Accuracy	0.1%
Transient Time Accuracy	10.0% ± 50% of Minimum Time
Remote Interface	GPIOB / RS-232 / ETHERNET / USB

### General


Derating for higher temperatures	(-).167% Rated Power / °C
AC Input	95~240 Vac 48~62 Hz
Power Consumption	130 VA
Operating Temperature	5 °C ~ 40 °C
Dimension	24.5"(L)x17"(W)x5.25"(H)
Weight	70 lbs      31.8 kg
Approx.Shipping Weight	108 lbs      49.0 kg

Ver 4.1      Date: 11/01/07

\*1 All Mode Specification measure by slow band and 25°C room temperature unless otherwise specified  
\*2 Transient Mode Specification must be x2  
AMREL reserves the right to change limits, test conditions, and dimensions without notice



PLA2.5K-600-120 (600V,120A,2.5KW) OPERATIONAL CURVE



Distributed By:  
Signal Test, Inc  
1529 Santiago Ridge Way  
San Diego, CA 92154  
Tel. 1-619-575-1577 USA  
www.SignalTestInc.com  
Sales@SignalTestInc.com



www.amrel.com Intl. 626 443-6818 U.S./Canada 800 654-9838