

Constant Voltage Mode

CVH Range	0.000 ~ 60.00	V
CVM Range	0.000 ~ 30.00	V
CVL Range	0.000 ~ 6.000	V
Transient Time Range		
Fast Band(Default,Osc1)	0.500 ~ 51.19	ms
Slow Band(Osc2,Osc3)	0.500 ~ 511.9	ms
Temperature Coefficient	100 ppm / °C of Rated Voltage	
Program		
CV Resolution*2	1/16000 of Rated Voltage	
CVH Accuracy*2	0.05% ± 0.060	V
CVM Accuracy*2	0.05% ± 0.060	V
CVL Accuracy*2	0.05% ± 0.060	V
Display		
CVH Resolution	1/16000 of Rated Voltage	
CVH Accuracy	0.05% ± 0.060	V
CVM Accuracy	0.05% ± 0.060	V
CCL Accuracy	0.05% ± 0.060	V

Constant Current Mode

CCH Range	0.000 ~ 1,500	A
CCM Range	0.000 ~ 750.0	A
CCL Range	0.000 ~ 150.0	A
Transient Time Range		
Fast Band(Default,Osc1)	0.050 ~ 51.19	ms
Slow Band(Osc2,Osc3)	0.500 ~ 511.9	ms
Minimum Voltage(I _{Max})	0.450	V
Temperature Coefficient	100 ppm / °C of Rated Current	
Program		
CC Resolution*2	1/16000 of Rated Current	
CCH Accuracy*2	0.05% ± 1.500	A
CCM Accuracy*2	0.05% ± 1.500	A
CCL Accuracy*2	0.05% ± 1.500	A
Display		
CC Resolution	1/16000 of Rated Current	
CCH Accuracy	0.05% ± 1.500	A
CCM Accuracy	0.05% ± 1.500	A
CCL Accuracy	0.05% ± 1.500	A

Programmable Protection

Power(OPP)		
Range	47.25 ~ 37,800	W
Resolution	4.725	W
Accuracy	0.50% ± 94.50	W
Voltage(OVP)		
Range	0.039 ~ 63.00	V
Resolution	0.004	V
Accuracy	0.20% ± 0.079	V
Current(OCP)		
Range	0.984 ~ 1,575	A
Resolution	0.098	A
Accuracy	0.20% ± 1.969	A
Under Voltage Lockout(UVL)		
Mode	Input On / Continuous	
Range	0.045 ~ 60.00	V
Resolution	0.015	V
Accuracy	2.50% ± 0.075	V
Anti-Oscillation	Default / Osc1 / Osc2 / Osc3 / Disable	

Protection

Over Power Protection(OP)	37,800 ± 720.0	W
Over Voltage Protection(OV)	63.00 ± 1.200	V
Over Current Protection(OC)	1,650 ± 15.71	A
Over Temperature Protection(OTP)	50.00 ± 5.000	°C
Reverse Maximum Current(RCP)	1,650	A
Short Maximum Current	1,530	A
Remote Inhibit(RI)	Short	
Fault Indicator	SPDT Relay (30Vdc/0.5A or 125Vac/0.25A)	

Dielectric Strength

Primary Circuit To Chassis	1500 Vac for 1 min
Primary Circuit To Load Terminal	1500 Vac for 1 min
Load Terminal To Chassis	1500 Vdc for 1 min

Constant Power Mode

CPH Range	0.000 ~ 36,000	W
CPM Range	0.000 ~ 18,000	W
@ lin	≤ 750.0	A
CPL Range	0.000 ~ 3,600	W
@ lin	≤ 150.0	A
Transient Time Range		
Same As CC Mode		
Temperature Coefficient	300 ppm / °C of Rated Power	
Program		
CP Resolution*2	1/16000 of Rated Power	
CPH Accuracy*2	1.00% ± 180.0	W
@lin	> 75.00	A
& Vin	> 6.000	V
CPM Accuracy*2	1.00% ± 180.0	W
@lin	> 15.00	A
& Vin	> 6.000	V
CPL Accuracy*2	1.00% ± 180.0	W
@lin	> 1.500	A
& Vin	> 12.00	V

Constant Resistance Mode

CRH Range	0.4000 ~ 20.00	Ω
@ lin	≤ 150.0	A
CRM Range	0.0400 ~ 10.00	Ω
CRL Range	0.0003 ~ 0.0400	Ω
Transient Time Range		
CRM / CRH	Same As CC Mode	
CRL	Same As CV Mode	
Temperature Coefficient	300 ppm / °C of Minimum Resistance	
CRL	300 ppm / °C of Maximum Resistance	
Program		
CR Resolution*2	1/16000 Of Rated Value	
CRH Accuracy*2	1.00% ± 12.50	mS
@lin	> 1.500	A
& Vin	> 12.00	V
CRM Accuracy*2	1.00% ± 50.00	mS
@lin	> 15.00	A
& Vin	> 6.000	V
CRL Accuracy*2	1.00% ± 0.040	mΩ
@lin	> 150.0	A
& Vin	> 0.060	V

External Programming Mode

Analog Program	0~10 Volts Input yields
Accuracy	0~selected full scaled loading in all modes
Input Impedance	Same As Internal ± 0.1% Rating
BandWidth(-3dB)	400 kΩ ± 1%
Monitor output Signal	Limited By Internal Transient Time
VMON Accuracy	0~10 Volts output for 0~full scaled Value
IMON Accuracy	0.10% ± 0.060 V
Transient Mode	0.10% ± 1.500 A
Frequency Range	0.100 ~ 10,000 Hz
Accuracy	0.1%
Duty Range	1.000 ~ 100.0 %
Accuracy	0.1%
Transient Time Accuracy	10.0% ± 50% of Minimum Time
Remote Interface	GPIOB / RS-232 / ETHERNET / USB


General

Fluid	
Valve	Normal Close(Power On Thermal Control)
Flow Rate(Pmax)	≥ 9.0 GPM @ 15°C Fluid In
Derating for higher temperatures	(-)3% Rated Power / °C
Pressure	<80 PSI
Pipe Size	Dual 1/2"(3/4"-Manifold) NPT Female
Decondensation	Valve Thermal Control
AC Input	95~240 Vac 48~62 Hz
Power Consumption	160 VA
Operating Temperature	5 °C ~ 40 °C
Dimension	27.5"(L)x17"(W)x7.0"(H)
Weight	160 lbs 72.6 kg
Approx.Shipping Weight	180 lbs 81.6 kg

*1 All Mode Specification measure by slow band and 25°C room temperature unless otherwise specified
 *2 Transient Mode Specification must be x2
 AMREL reserves the right to change limits, test conditions, and dimensions without notice



PLW36K-60-1500 (60V,1500A,36KW) OPERATIONAL CURVE



Distributed By:
Signal Test, Inc
1529 Santiago Ridge Way
San Diego, CA 92154
Tel. 1-619-575-1577 USA
www.SignalTestInc.com
Sales@SignalTestInc.com



www.amrel.com Intl. 626 443-6818 U.S./Canada 800 654-9838