Distributed By:
Signal Test, Inc
1529 Santiago Ridge Way
San Diego, CA 92154
Tel. 1-619-575-1577 USA
www.SignalTestInc.com
Sales@SignalTestInc.com



#### Use Model PRO-50A for:

Field Service

- Electronics
- Electrical

Calibration & Repair Service

Design Engineering

**Production Test** 

**Quality Control** 

# Test Equipment

**Digital Multimeter** 

## Model PRO-50A Hand-Held Digital Multimeter



The Global Specialties Model PRO-50A is a highly versatile, economically-priced, hand-held digital multimeter. Designed to meet CAT III (1000V) and CAT IV (600V) safety standards, Engineers, technicians, electricians and students can use the PRO-50A in confidence with its rugged design and non-contact AC voltage (NCV) detection feature. The PRO-50A has a large, 3 ½ digit LCD backlit display for comfortable viewing and is capable of measuring voltage, resistance, amperage, capacitance, frequency, transistors and temperature.

#### **Features:**

- 3 ½ Digit Backlit Display
- Non-contact AC voltage detection (NCV)
- 10A fused and full overload protection
- Data hold and Auto Power-Off
- Protective rubber boot
- Meets IEC1010-1, Cat III 1000V Cat IV 600V Safety Standards

### **Technical Specifications:**

**DCV:** 200m/2/20/200/1000V, <u>+</u>0.5%

**ACV:** 2/20/200/750V, +0.8% **DCA:** 20m/200m/10A, ±1.0% **ACA:** 20m/200m/10A, ±1.0% **OHM:** 200/2k/20k/200k/2M/20M/

 $200M\Omega$ ,  $\pm 1.0\%$ 

**CAP:** 20n/200n/2µ/200µF, ±3.0%

**FREQ:** 20kHz, <u>+</u>3.0%

**TEMP:** -20°C - 1000°C, <u>+</u>3.0%

**NCV:** ≥50V AC (TRMS)

**Audible Continuity and Diode Test** 

Transistor hfe test: 0 - 1000 Battery: 9V (1 each), 6F22 Dimensions: 7.4" x 3.6" x 2" Accessories: k-type temperature

probe

