

# Overhead Ionizing Blower



## Model IN5130

*Ptec™ Overhead Ionizer*

### *Piezo AC Ionization: Powerful, Balanced and Efficient*

#### **Features**

- Ptec™ Technology
- High Frequency AC (68KHz) ion emission
- Removable front grill
- Alarm indicators
- Variable speed output and on-off switch

#### **Benefits**

- Inherently stable output. Does not require calibration
- Reduces emitter cleaning. Extends emitter life. Dense ion output
- Easy to service emitters
- Red light illuminates to alert high voltage failure (on each fan)
- Delivers the correct air-flow for each application when needed


#### **Ptec™ Stability**

The IN5130 overhead ionizing blower combines exceptionally fast static decay capability with excellent balance stability, without taking valuable work-space. Designed to protect most static sensitive devices, the IN5130 uses a specialized piezoceramic technology that makes all the Ptec™ ionizers so reliable.

#### **Maintenance Savings**

Ptec™ ionizers save time and money because they require no calibration. Emitter life is increased and maintenance frequency is reduced, due to 68KHz AC ion emission.

### Model IN5130 Ptec™ Specifications

<b>Power Input</b>	24 VDC, 36W
<b>Power Outlet</b>	un-fused, 0.5A or 1.0A max.
<b>Ion Emission</b>	AC, 68KHz
<b>Balance</b>	±10 volts
<b>Decay Time</b>	1000V—100V, < 6 seconds @ 24"
<b>Temperature</b>	66-78°F (19-25°C)
<b>Humidity</b>	20-60% RH (non-condensing)
<b>Airflow</b>	115 cfm per fan, High speed
<b>Noise Level</b>	60dB(A) (Distance 1 meter)
<b>Indicators</b>	Power: Green LED, Alarm: Red
<b>Controls</b>	On/off switch, variable fan speed
<b>Mounting</b>	(4) four S hooks provided
<b>Emitter Points</b>	Tungsten Alloy
<b>Dimensions</b>	2.5"H x 39.4"W x 5.75D, (64 x 1000 x 146 cm)
<b>Weight</b>	11.5lbs, (5.0kg)
<b>Warranty</b>	1-year limited warranty
<b>Certifications</b>	



*Emitters are made of a special tungsten alloy and are replaceable. AC operation of the ionizer assures a long service life.*

### **Ptec™ Overhead Ionization**

A specialized piezoceramic high voltage transformer drives the technology making Ptec™ ionizers among the most reliable ionizers available. The model IN5130 overhead static eliminator produces a 68KHz AC output of approximately 2200V and a continuous stream of balanced air ions. Stable, small and lightweight, Ptec™ products detect and alarm if the high voltage output fails.

Ionizers that use Ptec™ technology do not require calibration and only minimal maintenance.

*The removable grill on the IN5130 simplifies emitter maintenance.*



### **Transforming Technologies, LLC**

Since 1998, Transforming Technologies has provided critical solutions to the numerous manufacturing problems associated with static electricity.

Transforming Technologies provide a wide range of unique and outstanding products to detect, protect, eliminate and monitor electrostatic charges. Our products are key tools used by industry to assure an effective static control program.

**Distributed By:**  
**Signal Test, Inc**  
1529 Santiago Ridge Way  
San Diego, CA 92154  
Tel. 1-619-575-1577 USA  
www.SignalTestInc.com  
Sales@SignalTestInc.com

**SIGNAL TEST™**  
New & Used Test Equipment